

## MAGIC MOMENT

|                   |   |
|-------------------|---|
| CONSTRUCTION      | CUT PILE                                  |
| FIBRE COMPOSITION | 100% Solution Dyed Polyester              |
| PILE WEIGHT       | 2100 g/m <sup>2</sup>                     |
| TOTAL WEIGHT      | 3100 g/m <sup>2</sup> +/-5%               |
| TUFT GAUGE        | 1/8"                                      |
| TUFT DENSITY      | 195300/sqm                                |
| PRIMARY BACKING   | Woven                                     |
| SECONDARY BACKING | Fleece Backing                            |
| CARPET WIDTH      | 3.66m or 4.00m                            |
| PILE HEIGHT       | 15.00mm                                   |
| TOTAL HEIGHT      | 17.0mm                                    |
| PILE TREATMENT    | UV Treated Yarn , Walk Of Fame (Optional) |

## PERFORMANCE SPECS

|                |                                 |                                       |
|----------------|---------------------------------|---------------------------------------|
| VOC EMISSIONS  | ASTM D5116-17                   | <0.5mg/m <sup>2</sup> /hour (CRI GLP) |
| FLAMMABILITY   | ASTM D-2859//FF1-70//16CFR 1630 | PASS 8/8                              |
| COLOR FASTNESS | ISO 105 B02:2014                | 4/5 on Grey Scale                     |



- Shading or Pile reversal is an inherent attribute of cut pile carpets and it is not a manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of ± 5%
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies



Standard Carpets Ind LLC  
 P.O. Box No. 490014  
 Dubai Industrial Park, Dubai UAE  
 T: +971 4 554 7137 | F: +971 4 554 7132  
 E: info@standardcarpets.com | www.standardcarpets.com

Made In The UAE. The largest manufacturer of tufted carpets and the only manufacturer of carpet tiles in the United Arab Emirates.

Standard Carpets are manufactured under the environmental quality system certified and complying with ISO 45001 by an accredited certification body.